



# ZEKE



## Technical Rider + ZEKE ENGINEER NOTES

The venue or promoter will provide a professional soundman and monitor engineer at their expense.

Zeke needs to have a PA capable of handling up to 16 inputs plus 4 separate monitor mixes

**MONITOR REQUIREMENTS (Bi-amped):** at least 2 JBL SRX712m floor wedges or equivalent, 1 JBL SRX 725 Drumfill or equivalent. **MONITOR POWER** at least 1 QSC PLX 3002 (900w/ch @ 4 ohms) amp - for Wedges or equivalent and 1 QSC PLX 2402 (1100w/ch @ 4 ohms) amp – for Drumfill or equivalent .

**\*\*See separately attached stage plot / input list \*\***

### Band Member Names:

Marky - Lead Vocals and Lead Guitar V1

Jeff - Backing Vocals and Guitar

Jason - Bass

Donny - Drums

We are a fast loud punk band – Marky's Lead Vocals and Lead Guitar is our focal point. Jeff sings some lead parts and backups please keep him up in the mix, we are very loud, but will try to work with you to get the best sound.

### MONITORS ( in order of importance):

#### MIX 1 Marky

Lead Vocals V1 = Marky

Snare

Kick

#### Mix 2 Jeff

Lead Vocals V1 = Marky

V2 Vocals = Jeff

Snare

Kick

#### Mix 3 Jason

Lead Vocals V1 = Marky

Snare

Kick

#### Mix 4 Donny

Lead Vocals V1 = Marky

Lead Guitar

Snare

Kick LOUD

**Note: absolutely no compression on guitar and very light Gate on Bass Drum Mic, some hits are soft**